TOWN OF MARBLETOWN

P.O. BOX 217 STONE RIDGE, NY 12484 845-687-7500 ext 104 codeman@marbletown.net

APPLICATION FOR BED AND BREAKFAST

PROPERTY OF: STREET ADDRESS MAILING ADDRE	S: SS:			
PHONE NO.:	E			
SECTION:	BLOCK:	LOT:	ZONING DISTRICT	V
NUMBER OF BED	ROOMS FOR GUE	STS (3 minimum, fi	ive maximum)	
NUMBER OF PARI NUMBER OF PARI			er guest room)	
PROPOSED SIGNS	*: N Y, _	ROAD SIDE	ON BUILDING	ВОТН
ADDITIONAL LIG	HTING*: N N	Y,F G LOTON	FOR SIGNS WAL BUILDING	KWAY
			all existing structures, local	tion of
		And		
Comply with	n <i>RESIDENTIAL C</i>	CODE OF NYS (20)	10 code cycle)** requirement	nts.
SIGNATURE:			DATE:	
Office use only				
Referred to:	Planning Board	Zoning Board	Date:	
Paid by:	Chec	k number:	Bank:	

**STATE RESIDENTIAL CODE REQUIREMENTS FOR BED AND BREAKFAST SEE PAGE TWO

§RAJ704 BED AND BREAKFAST DWELLINGS

- §RAJ704.1 Scope. Owner-occupied one-family dwellings converted for use as bed and breakfast dwellings as defined in §RAJ202 shall comply with this section.
- **SRAJ704.2 Occupancy.** A residence converted to a bed and breakfast dwelling shall have no more than five sleeping rooms for accommodating up to 10 transient lodgers.
- **SRAJ704.3 Special conditions.** A one-family dwelling is permitted to be converted for use as a bed and breakfast dwelling under the following conditions:
 - 1. No sleeping rooms for transient use shall be located above the second story.
 - 2. A fire-safety notice shall be affixed to the occupied side of the entrance door of each bedroom for transient use indicating:
 - 1. Means of egress;
 - 2. Location of means for transmitting fire alarms, if any; and
 - 3. Evacuation procedures to be followed in the event of a fire or smoke condition or upon activation of a fire or smokedetecting or other alarm device.
- **\$RAJ704.4 Means of egress.** Means of egress shall include at least one of the following alternatives:
 - 1. A limited area sprinkler system installed in conformance with NFPA 13D protecting all interior stairs serving as a means of egress;
 - 2. An exterior stair conforming to the requirements of §RR311.1 and §RR311.5 of this code, providing a second means of egress from all above grade stories or levels; or
 - 3. An opening for emergency use conforming to the requirements of §RR310 of this code within each bedroom for transient use, such opening to have a sill not more than 14 feet above level grade directly below and, as permanent equipment, a portable escape ladder that attaches securely to such sill. Such ladder shall be constructed with rigid rungs designed to stand off from the building wall, shall be capable of sustaining a minimum load of 1,000 pounds, and shall extend to and provide unobstructed egress to open space at grade."